



Canopy LB8F H: 4.50 W: 9 3/8

Description

Round LED Surface Mount

Specifications

Housing	Injection-molded polycarbonate
Diffuser/Optics	Frosted Polycarbonate
Light Source	LED
Max Watts	18
Electrical Mounting	DOB - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board. Mounts over 4" recessed outlet box
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	<u>LB8F</u>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Frosted Polycarbonate

Light Source

L13 DOB - 13W/30K 910 lumen LED
L14 DOB - 14W/30K 1350 lumen LED
L18 LTE 40K - 18W/40K 1824 lumen LED

Finish

Standard
BL - Black
WH - White

Extras (Order Separately)

OSUHF - Occupancy Sensor
 Hidden behind diffuser
PCL1 - Factory-installed 120V
 PHOTOCELL - Only available
 with LED Light Sources.