



**Canopy LB8F** H: 4.50 W: 9 3/8

**Description**

Round LED Surface Mount

**Specifications**

- Housing** Injection-molded polycarbonate
- Diffuser** Frosted Polycarbonate
- Light Source** LED
- Max Watts** 18
- Electrical** DOB - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board.
- Mounting** Mounts over 4" recessed outlet box
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations

**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide	LB8F				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser**  
Frosted Polycarbonate

**Light Source**  
**L13 DOB** - 13W/30K 910 lumen LED  
**L14 DOB** - 14W/30K 1350 lumen LED  
**L18 LTE 40K** - 18W/40K 1824 lumen LED

**Finish**  
**Standard**  
**BL** - Black  
**WH** - White

**Extras (Order Separately)**  
**OSUHF** Occupancy Sensor Hidden behind diffuser  
**PCL1** Factory-installed 120V PHOTOCELL - Only available with LED Light Sources.