

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_



**Canopy LB8W** H: 4.50 W: 9 3/8

**Description**

10" Round LED Surface Mount

**Specifications**

Housing	Injection-molded polycarbonate
Diffuser/Optics	White Polycarbonate
Light Source	LED
Max Watts	23
Electrical Mounting	DOB - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board. Mounts over 4" recessed outlet box
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations

**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide	<u>LB8W</u>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**  
White Polycarbonate

**Light Source**  
**L13 DOB** - 13W/30K 910 lumen LED  
**L14 DOB** - 14W/30K 1350 lumen LED  
**L18 LTE 40K** - 18W/40K 1824 lumen LED  
**L23 DOB** - 23W/30K 1850 lumen LED

**Finish**  
**Standard**  
**BL** - Black  
**WH** - White

**Extras (Order Separately)**  
**OSUHF** - Occupancy Sensor  
 Hidden behind diffuser  
**PCL1** - Factory-installed 120V  
 PHOTOCELL - Only available  
 with LED Light Sources.