



Area/Bollard LF240F H: 27 W: 20.50

Description

For those applications requiring a modern post-style, look to the LF240's from Luraline to give you what you need. A unique fixture for sure, this is both distinct and durable. Made with a cast aluminum housing, this LED fixture emits up to 6,000 lumens while using only 60 watts. The body can be ordered in black, white or bronze, while the acrylic lens is a frosted flat panel. LF204D features a white Drop-lens.

Specifications

- Housing Die-cast aluminum
- Diffuser/Optics Flat Frosted Acrylic Lens
- Light Source LTE
- Max Watts 60
- Electrical LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
- Mounting Slips 3" OD - Order Separately
- Certification Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations



Ordering Guide: Choose from each category, using designated code to specify.

LF240F				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- Frosted Acrylic

Light Source

L4000C - 40W/40K 4000 lumen LED
L6000C - 60W/40K 6000 lumen LED

Finish

Standard
B - Textured Black
Upgraded*
W - Textured White
Z - Textured Bronze
 * Subject to Surcharge

Extras (Order Separately)

GSS 10 KV Ground Surge Supression (120-277V)