



**Canopy LFRC30 CM** H: 4" W: 18"

**Description**

**Specifications**

- Housing** Die Cast Aluminum housing.
- Diffuser/Optics**
  - Clear Polycarbonate (Type II)
  - Clear Polycarbonate (Type III)
  - Clear Polycarbonate (Type IV)
  - Clear Polycarbonate (Type V)
- Light Source** LTE
- Max Watts** 159.2
- Electrical Mounting** LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver. Mounts over 4" recessed outlet box.
- Certification**



**Ordering Guide:** Choose from each category, using designated code to specify.

LFRC30 CM					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

- C2** - Clear Polycarbonate (Type II)
- C3** - Clear Polycarbonate (Type III)
- C4** - Clear Polycarbonate (Type IV)
- C5** - Clear Polycarbonate (Type V)

**Light Source**

- L37 LTE 40K** - 42.2W/40K 5,100 lumen LED
- L140 LTE 40K** - 159.2W/40K 21,000 lumen LED

**Finish**

- Standard**
- W** - White

**Extras (Order Separately)**

- (D) FUSE** DOUBLE FUSED
- (S) FUSE** SINGLE FUSED
- 50K** Daylight
- (Non-Stock item - consult factory for availability)