



**Wall Pack/Floodlight LH103** H: 15.25" W: 7.4" E: 9" MC: 2.75"

**Description**

Wall Mount LED Lantern

**Specifications**

<b>Housing</b>	Injection-molded polypropylene	
<b>Diffuser/Optics</b>	Frosted Acrylic Lens	
<b>Light Source</b>	DOB	Medium Base
<b>Max Watts</b>	13	60
<b>Electrical</b>	<b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. <b>DOB</b> - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board.	
<b>Mounting</b>	Mounts over 4" recessed outlet box.	
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations	



**Ordering Guide:** Choose from each category, using designated code to specify.

LH103					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**  
F - Frosted Acrylic Lens

**Light Source**  
L13 DOB - 13W/30K 1140 lumen LED  
MB - Maximum 60W A (by others)

**Finish**  
**Standard**  
B - Black  
W - White  
Z - Bronze (94)

**Extras (Order Separately)**  
40K  
PC1 Field installed 120V PHOTOCELL