



Area/Bollard LH231 H: 26.75 W: 11.50

Description

Traditional style combined with long-lasting craftsmanship and materials. That's what you get with this area fixture from Luraline. The four-panel classic shape makes this fixture ideal for almost any application, including parks, recreation areas, parking lots, commercial complexes, and retail areas. The LED light source emits up to 6,000 lumens while using only 60 watts. The body can be ordered in black, white or bronze, while the acrylic lens is available in either white or clear prismatic. Also available are optional blackout panels.

Specifications

- Housing** Die-cast aluminum
- Diffuser/Optics**
 - Clear Prismatic Acrylic
 - White Acrylic
- Light Source** LTE
- Max Watts** 60
- Electrical** LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
- Mounting** Slips 3" OD - Order P Series Poles separately
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations



Ordering Guide: Choose from each category, using designated code to specify.

LH231					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

- C** - Clear Prismatic Acrylic
- W** - White Acrylic

Light Source

- L4000C** - 40W/40K 4000 lumen LED
- L6000C** - 60W/40K 6000 lumen LED

Finish

- Standard**
- B** - Textured Black
- Upgraded***
- W** - Textured White
- Z** - Textured Bronze
- * Subject to Surcharge

Extras (Order Separately)

- B1** 1 Blackout Panel
- B2** 2 Blackout Panels
- B3** 3 Blackout Panels