



Wall Pack/Floodlight LR121 H: 15" W: 6.125" E: 6.75" MC: 6.5"

Description

Wall Mount LED Lantern

Specifications

- Housing** Injection-molded polypropylene
- Diffuser/Optics** Frosted Acrylic Lens
- Light Source** DOB Medium Base
- Max Watts** 13 60
- Electrical**
 - MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
 - DOB** - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations



Ordering Guide: Choose from each category, using designated code to specify.

| | | | | | |
|-------|----------|--------------|--------|--------|--|
| LR121 | | | | | |
| MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS | |

Diffuser/Optics
F - Frosted Acrylic Lens

Light Source
L13 DOB - 13W/30K 900 lumen LED
MB - Maximum 60W A (by others)

Finish
Standard
B - Black
W - White
Z - Bronze (94)

Extras (Order Separately)
40K
PC1 Field installed 120V PHOTOCELL