



Wall Pack LTV2FP H: 7.88 W: 6.63 E: 4.5

Description

COB FlushPack

Specifications

- Housing** Constructed of die cast aluminum.
- Diffuser** Opalescent polycarbonate
- Light Source** LED
- Max Watts** 43
- Electrical** COB - Includes 50,000 Hr. COB LED module with 120-277V HPF 0-10V dimmable constant current driver.
- Mounting** Mounts over 4" recessed box or 1/2" surface conduit.
- Certification**

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	<u>LTV2FP</u>				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

- | | | | |
|--|--|--|--|
| <p>Diffuser</p> <p>Opalescent (white) polycarbonate</p> | <p>Light Source</p> <p>L21 COB 41K - 21.1W/41K 2169 lumen LED</p> <p>L43 COB 41K - 42.7W/41K 3729 lumen LED</p> | <p>Finish</p> <p>Standard</p> <p>ZT - Bronze (textured)</p> | <p>Extras (Order Separately)</p> <p>GSS 10 KV Ground Surge Supression (120-277V)</p> |
|--|--|--|--|

NOTES: Wall Mount ONLY