



**Wall Pack** LTV2FP H: 7.88 W: 6.63 E: 4.5

**Description**

COB FlushPack

**Specifications**

Housing	Constructed of die cast aluminum.
Diffuser/Optics	Opalescent polycarbonate
Light Source	LED
Max Watts	43
Electrical	COB - Includes >50,000 Hr. COB LED module with 120-277V HPF 0-10V dimmable constant current driver.
Mounting	Mounts over 4" recessed box or 1/2" surface conduit.
Certification	

**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide	<u>LTV2FP</u>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

<b>Diffuser/Optics</b>	<b>Light Source</b>	<b>Finish</b>	<b>Extras (Order Separately)</b>
Opalescent (white) polycarbonate	<b>L21 COB 41K</b> - 21.1W/41K 2169 lumen LED <b>L43 COB 41K</b> - 42.7W/41K 3729 lumen LED	<b>Standard</b> <b>ZT</b> - Bronze (textured)	<b>GSS</b> 10 KV Ground Surge Supression (120-277V)

NOTES: Wall Mount ONLY