



**Wall Pack/Floodlight LTV3FL** H: 11.25 W: 9.75 E: 13.38

## Description

COB FloodPack

## Specifications

- Housing** Constructed of die cast aluminum with heavy-duty adjustable slip fitter.
- Diffuser/Optics** Clear Glass
- Light Source** COB
- Max Watts** 80.2
- Electrical** COB - Includes >50,000 Hr. COB LED module with 120-277V HPF 0-10V dimmable constant current driver.
- Mounting** Mounts over 4" recessed outlet box.
- Certification**



**Ordering Guide:** Choose from each category, using designated code to specify.

LTV3FL				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**  
Clear Flat Glass

**Light Source**  
**L56 COB 41K** - 56.2W/41K 5301 lumen LED  
**L80 COB 41K** - 80.2W/41K 7031 lumen LED

**Finish**  
**Standard**  
**ZT** - Bronze (textured)

**Extras (Order Separately)**  
**(D) FUSE** DOUBLE FUSED  
**(S) FUSE** SINGLE FUSED  
**PCL1** Factory-installed 120V PHOTOCELL - Only available with LED Light Sources.  
**SSP** 10KV 120-277V Supplemental Surge Protection

NOTES: Wall Mount ONLY