



Bulkhead LWPR25GR H: 12.5 W: 12.5 E: 4.25

Description

12.5" Round Grid Frame Bulkhead

Specifications

- Housing** Constructed of die cast aluminum and finished with a bronze powdercoat.
- Diffuser/Optics** Opalescent polycarbonate
- Light Source** LED
- Max Watts** 19.7
- Electrical Mounting** LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver. Mounts over 4" recessed box or 1/2" surface conduit.
- Certification**



Ordering Information Choose one from each category, filling in the guide using designated code.

| | | | | | |
|-------|-----------------|-------------|--------------|-------------|-------------|
| Guide | <u>LWPR25GR</u> | <u> </u> | <u> </u> | <u> </u> | <u> </u> |
| | MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |

Diffuser/Optics
Opalescent (white) polycarbonate

Light Source
L20 LTE 50K - 19.7W/50K 2539 lumen LED

Finish
Standard
WT - White (textured)
ZT - Bronze (textured)

Extras (Order Separately)
BBL 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)

NOTES: Wall Mount ONLY