



Bulkhead LWPR25OF H: 12.5 W: 12.5 E: 3.94

Description

12.5" Round Open Frame Bulkhead

Specifications

- Housing** Constructed of die cast aluminum and finished with a bronze powdercoat.
- Diffuser** Opalescent polycarbonate
- Light Source** LED
- Max Watts** 19.7
- Electrical** LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
- Mounting** Mounts over 4" recessed box or 1/2" surface conduit.
- Certification**



Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	LWPR25OF				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

- | | | | |
|--|---|--|--|
| <p>Diffuser</p> <p>Opalescent (white) polycarbonate</p> | <p>Light Source</p> <p>L20 LTE 50K - 19.7W/50K 2539 lumen LED</p> | <p>Finish</p> <p>Standard</p> <p>WT - White (textured)</p> <p>ZT - Bronze (textured)</p> | <p>Extras (Order Separately)</p> <p>BBL 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)</p> |
|--|---|--|--|

NOTES: Wall Mount ONLY