



Bulkhead LWPR25OF H: 12.5 W: 12.5 E: 3.94

Description

12.5" Round Open Frame Bulkhead

Specifications

- Housing** Constructed of die cast aluminum and finished with a bronze powdercoat.
- Diffuser/Optics** Opalescent polycarbonate
- Light Source** LED
- Max Watts** 19.7
- Electrical** LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
- Mounting** Mounts over 4" recessed box or 1/2" surface conduit.
- Certification**



Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	<u>LWPR25OF</u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics
Opalescent (white) polycarbonate

Light Source
L20 LTE 50K - 19.7W/50K 2539 lumen LED

Finish
Standard
WT - White (textured)
ZT - Bronze (textured)

Extras (Order Separately)
BBL 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)
PC1 Field installed 120V PHOTOCELL
PC2 Field installed 277V PHOTOCELL

NOTES: Wall Mount ONLY