



**Bulkhead** LWPR25OF H: 12.5 W: 12.5 E: 3.94

**Description**

12.5" Round Open Frame Bulkhead

**Specifications**

- Housing** Constructed of die cast aluminum and finished with a bronze powdercoat.
- Diffuser** Opalescent polycarbonate
- Light Source** LED
- Max Watts** 19.7
- Electrical** LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
- Mounting** Mounts over 4" recessed box or 1/2" surface conduit.
- Certification**



**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide	LWPR25OF				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

- |  |   |  |  |
|--|---|--|--|
| <p><b>Diffuser</b></p> <p>Opalescent (white) polycarbonate</p> | <p><b>Light Source</b></p> <p><b>L20 LTE 50K</b> - 19.7W/50K 2539 lumen LED</p> | <p><b>Finish</b></p> <p><b>Standard</b></p> <p><b>WT</b> - White (textured)</p> <p><b>ZT</b> - Bronze (textured)</p> | <p><b>Extras (Order Separately)</b></p> <p><b>BBL</b> 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)</p> |
|--|---|--|--|

NOTES: Wall Mount ONLY