



**Bulkhead** LWPS250F H: 12.5 W: 12.5 E: 3.94

### Description

12.5" Square Open Frame Bulkhead

### Specifications

**Housing** Constructed of die cast aluminum and finished with a bronze powdercoat.

**Diffuser/Optics** Opalescent polycarbonate

**Light Source** LED

**Max Watts** 19.7

**Electrical** LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.

**Mounting** Mounts over 4" recessed box or 1/2" surface conduit.

### Certification



**Ordering Guide:** Choose from each category, using designated code to specify.

LWPS250F					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

#### Diffuser/Optics

Opalescent (white) polycarbonate

#### Light Source

**L20 LTE 50K** - 19.7W/50K 2539 lumen LED

#### Finish

**Standard**  
**WT** - White (textured)  
**ZT** - Bronze (textured)

#### Extras (Order Separately)

**(D) FUSE** DOUBLE FUSED  
**(S) FUSE** SINGLE FUSED  
**BBL** 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)  
**PC1** Field installed 120V PHOTOCELL  
**PC2** Field installed 277V PHOTOCELL  
**SSP** 10KV 120-277V Supplemental Surge Protection