



**Legacy Product** **QS12HB** H: 6 W: 12

**Description**

12" Quarter-sphere sconce

**Specifications**

Light Source	Fluorescent	Medium Base
Max Watts	42	60
Electrical	<b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. <b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures. <b>DOB</b> - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board.	
Mounting	Mounts over 4" recessed outlet box.	
Certification	Manufactured in accordance with U.L. standard 1598 -	

**Ordering Guide:** Choose from each category, using designated code to specify.

MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

**Light Source**

- F13 QE** - 13W/27K 900 lumen CF
- F26 QE** - 26W/27K 1800 lumen CF
- F32 TE** - 32W/30K 2400 lumen CF
- F42 TE** - 42W/30K 3200 lumen CF
- MB** - Maximum 60W A (by others)

**Finish**

- Standard**
- Upgraded\***
- RAL** - [Specify Color](#)
- UPG** - [Select Color](#)
- [Luraline Paint](#)
- Premium\***
- CCM** - Custom
- CIC** - [Inner Color](#)
- CTC** - [Clear Top](#)
- \* Subject to Su