



RLM RA11 GNL H: 19 W: 10.50 E: 19 MC: 3

Description

11" Angled, 11" L-arm

Specifications

Housing Spun aluminum shade with extruded arm and cast

Diffuser/Optics

- Bare lamp (no diffuser) for Dry locations only
- Clear tempered glass cylinder
- Frosted glass cylinder

Light Source GUL MBL Medium Base

Max Watts 11 13 100

Electrical

- MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
- MBL** - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.
- GUL** - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.

Mounting Mounts over 4" recessed outlet box.

Certification Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only) -



Ordering Guide: Choose from each category, using designated code to specify.

| | | | | |
|----------|----------|--------------|--------|--------|
| RA11 GNL | | | | |
| MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |

Diffuser/Optics

Bare-lamp (no diffuser)
CL - Clear glass
FR - Frosted Glass

Light Source

MB25 A - 25W MAX. MED base (A19 lamp by others)
MBL6A - 5.5W/30K 470 Lm OmniLED
MBL9.8A - 9.8W/30K 800 Lm OmniLED
MBL10A JAB - 10W/30K 800 Lm 90+ CRI OmniLED
MBL11A - 11W/30K 1100 Lm OmniLED
GUL11A - 11W/27K 1100 Lm GU24 OmniLED
MBL11A - 11W/30K 1100 Lm OmniLED
MBL13A JAB - 13W/30K 1100 Lm 90+ CRI OmniLED
MB - 100W Max Incand A (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

CG3 Cast aluminum guard (requires diffuser)
SSP 120 4KV 120V MOV1 Surge Suppressor