



Legacy Product RA9 GNA36X H: 21.3 W: 9.5

Description

MOQ may apply - please consult factory.
9" Angle shade, 36" Goosneck Arm

Specifications

Housing	Spun aluminum shade with extruded arm and cast canopy*
Diffuser/Optics	Frosted glass cylinder
Light Source	LED
Max Watts	9.62
Electrical	TL/HO- L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
Mounting	Mounts over 4" recessed outlet box.
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only)

Ordering Guide: Choose from each category, using designated code to specify.

RA9 GNA36X				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

FR - Frosted glass

Light Source

TL3 - 3.11W/30K 603 Lm, 0-10V dimmable
TL6 HO - 6.16W/40K 1588 Lm, 120V dimmable
TL6 - 6.32W/30K 1208 Lm, 120V dimmable
TL8 HO - 7.75W/40K 1886 Lm, 120V dimmable
TL8 - 7.96W/30K 1502 Lm, 120V dimmable
TL9 HO - 9.36W/40K 2179 Lm, 120V dimmable
TL10 - 9.62W/30K 1790 Lm, 120V dimmable

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

27K Non-Stock item - consult factory for availability
35K Neutral White
DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
SSP 10KV 120-277V Supplemental Surge Protection