



RLM RD14 P2 H: 25 W: 14 E: 41

Description

14" Deep Bowl, Double U-arm postlight (slips 3")

Specifications

Housing	Spun aluminum shade with extruded arm and cast fitter		
Diffuser/Optics	<ul style="list-style-type: none"> • Bare lamp (no diffuser) for Dry locations only • Clear glass • Frosted Glass cylinder 		
Light Source	GUL	MBL	Medium Base
Max Watts	15 X 2	110 X 2	200 X 2
Electrical	<p>MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.</p> <p>MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.</p> <p>GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.</p>		
Mounting	Slips 3" OD (PX Series) poles - order separately		
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only)		



Ordering Guide: Choose from each category, using designated code to specify.

RD14 P2					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

- Bare-lamp (no diffuser)
- CL** - Clear glass
- FR** - Frosted glass

Light Source

- 2MBL9.8A** - 19.6W/30K 1600 Lm OmniLED
- 2MBL10A JAS** - 20W/30K 1600 Lm 90+ CRI OmniLED
- 2GUL11A** - 22W/27K 2200 Lm GU24 OmniLED
- 2MBL15A** - 30W/30K 3200 Lm OmniLED
- 2GUL15A** - 30W/27K 3200 Lm GU24 OmniLED
- 2MB25A** - 2x 25W MAX. MED base (lamp by others)
- 2MBL11A** - 23W/30K 2280 Lm OmniLED
- MB** - Maximum 2x 200W A (by others)

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- CG3** Cast aluminum guard (requires diffuser)