



RLM RS16 GNU22 H: 30 W: 16 E: 29.50 MC: 22.75

Description

16" RLM, 22" U-arm

Specifications

| | | | |
|------------------------|--|-----|-------------|
| Housing | Spun aluminum shade with extruded arm and cast canopy | | |
| Diffuser/Optics | <ul style="list-style-type: none"> • Bare lamp (no diffuser) for Dry locations only • Clear tempered glass cylinder • FR - Frosted Glass | | |
| Light Source | GUL | MBL | Medium Base |
| Max Watts | 11 | 13 | 100 |
| Electrical | <p>MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.</p> <p>MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.</p> <p>GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.</p> | | |
| Mounting | Mounts over 4" recessed outlet box. | | |
| Certification | Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only) | | |



Ordering Guide: Choose from each category, using designated code to specify.

| | | | | |
|------------|----------|--------------|--------|--------|
| RS16 GNU22 | | | | |
| MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |

Diffuser/Optics

- Bare-lamp (no diffuser)
- CL** - Clear glass
- FR** - Frosted glass

Light Source

- MB25 A** - 25W MAX. MED base (A19 lamp by others)
- MBL6A** - 5.5W/30K 470 Lm OmniLED
- MBL9.8A** - 9.8W/30K 800 Lm OmniLED
- MBL11A** - 11W/30K 1100 Lm OmniLED
- GUL11A** - 11W/27K 1100 Lm GU24 OmniLED
- MBL11A** - 11W/30K 1100 Lm OmniLED
- MBL13A JA8** - 13W/30K 1100 Lm 90+ CRI OmniLED
- MB** - 100W Max Incand A (by others)

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- CG3** Cast aluminum guard (requires diffuser)