



**Legacy Product SH18 CM** H: 13.50 W: 18

**Description**

MOQ of 24 pcs. required

**Specifications**

<b>Housing</b>	Stamped steel fitter and canopy		
<b>Diffuser/Optics</b>	OP - Opal Glass		
<b>Light Source</b>	GUL	MBL	Medium Base
<b>Max Watts</b>	15	18	150
<b>Electrical</b>	<b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. <b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures. <b>GUL</b> - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.		
<b>Mounting</b>	Mounts over 4" recessed outlet box.		
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - For dry locations only		

**Ordering Guide:** Choose from each category, using designated code to specify.

SH18 CM                   

MODEL                      DIFFUSER                      LIGHT SOURCE                      FINISH                      EXTRAS

**Diffuser/Optics**

OP - Opal Glass

**Light Source**

- MB25 A** - 25W MAX. MED base (A19 lamp by others)
- MBL11A** - 11W/30K 1100 Lm OmniLED
- GUL15A** - 15W/27K 1600 Lm GU24 OmniLED
- MBL18A JAB** - 18W/30K 1600 Lm 90+ CRI OmniLED
- MB** - 150W Max Incand A (by others)

**Finish**

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**