



Legacy Product SH18 STEM H: 12 W: 18

Description

MOQ of 24 pcs. required or set up charge may apply - please consult factory.
18" School House pendant with 12" stem and 40° swivel canopy

Specifications

Housing	Stamped steel fitter and canopy*		
Diffuser/Optics	OP - Opal Glass		
Light Source	GUL	MBL	Medium Base
Max Watts	15	18	200
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures. GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.		
Mounting	Mounts over 4" recessed outlet box.		
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only		

Ordering Guide: Choose from each category, using designated code to specify.

SH18 STEM					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

OP - Opal Glass

Light Source

- MB25 A** - 25W MAX. MED base (A19 lamp by others)
- MBL9.8A** - 9.8W/30K 800 Lm OmniLED
- MBL11A** - 11W/30K 1100 Lm OmniLED
- GUL15A** - 15W/27K 1600 Lm GU24 OmniLED
- MBL15A** - 15./30K 1600 Lm OmniLED
- MBL18A JA8** - 18W/30K 1600 Lm 90+ CRI OmniLED
- MB** - Maximum 200W A (by others)

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)