



**Decorative** SOC96 CORD H: 3.25 W: 5 OAL: 100

**Description**

Bare-lamp socket pendant with 96" Black 18-3 SVT cord. (White cord supplied with white fixtures)

**Specifications**

Housing	Stamped steel cup, canopy		
Diffuser/Optics	Bare lamp (no diffuser)		
Light Source	GUL	MBL	Medium Base
Max Watts	15	18	100
Electrical	<b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. <b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.		
Mounting	Mounts over 4" recessed outlet box.		
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only		



**Ordering Guide:** Choose from each category, using designated code to specify.

SOC96 CORD					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

Bare-lamp (no diffuser)

**Light Source**

- MB25 A** - 25W MAX. MED base (A19 lamp by others)
- MBL6A** - 5.5W/30K 470 Lm OmniLED
- MBL10A JA8** - 10W/30K 800 Lm 90+ CRI OmniLED
- MBL11A** - 11W/30K 1100 Lm OmniLED
- GUL11A** - 11W/27K 1100 Lm GU24 OmniLED
- MBL13A JA8** - 13W/30K 1100 Lm 90+ CRI OmniLED
- GUL15A** - 15W/27K 1600 Lm GU24 OmniLED
- MBL15A** - 15./30K 1600 Lm OmniLED
- MBL18A JA8** - 18W/30K 1600 Lm 90+ CRI OmniLED
- MB** - 100W Max Incand A (by others)

**Finish**

- Standard**
- WH** - White
- Upgraded\***
- RAL** - [Specify Color #](#)
- UPG** - [Select Color from Luraline Palette](#)
- Premium\***
- CCM** - Custom Color
- CIC** - [Inner Color](#)
- CTC** - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**