



**Cylinder 260 CMXT** H: 8.88 W: 4.50

**Description**

4.5" Square surface-mounted cylinder  
Designed for use with uni-directional LED or reflector type (R/PAR) lamps

**Specifications**

- Housing** Extruded aluminum cylinder
- Diffuser/Optics** Clear tempered glass bottom lens
- Electrical** TL/HO- L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations

**Ordering Guide:** Choose from each category, using designated code to specify.



**Diffuser/Optics**  
Clear tempered glass

**Light Source**

**Finish**  
**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

**Extras (Order Separately)**  
**27K** Non-Stock item - consult factory for availability  
**35K** Neutral White  
**DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)  
**SSP** 10KV 120-277V Supplemental Surge Protection

NOTES: \*Driver is housed in extended aluminum canopy (not shown)