



## Cylinder 260 CORDT H: 8.88 W: 4.5 OAL: 45.75

### Description

4.5" Square cylinder, suspended by 36" Black 18-3 cord  
 (White cord supplied with white fixtures)  
 Designed for use with uni-directional LED or reflector type (R/PAR) lamps

### Specifications

<b>Housing</b>	Extruded aluminum cylinder with stamped steel canopy	
<b>Diffuser/Optics</b>	Clear tempered glass bottom lens	
<b>Light Source</b>	MBL	Medium Base
<b>Max Watts</b>	25	75
<b>Electrical</b>	<b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. <b>MBL</b> - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.	
<b>Mounting</b>	Mounts over 4" Recessed Outlet Box	
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - For dry locations only	



### Ordering Guide: Choose from each category, using designated code to specify.

260 CORDT					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

#### Diffuser/Optics

Clear tempered glass

#### Light Source

**MBL13 PAR FL** - 13W/30K 1000 Lm PAR30  
**MBL13 PAR SP** - 13W/30K 1000 Lm PAR30  
**MBL13 PAR WFL** - 13W/30K 1000 Lm PAR30  
**MB25 PAR** - 25W MAX. MED base (Par30 lamp by others)  
**MB** - Maximum 75W Par30 (by others)

#### Finish

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from  
     Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

#### Extras (Order Separately)

**SSP 120** 4KV 120V MOV1  
 Surge Suppressor