



Cylinder 260 STEMT H: 8.88 W: 4.5 OAL: 22.75

Description

4.5" Square cylinder, suspended by 12" stem with 40° swivel canopy
Designed for use with uni-directional LED or reflector type (R/PAR) lamps

Specifications

- Housing** Extruded aluminum cylinder with stamped steel canopy
- Diffuser/Optics** Clear tempered glass bottom lens
- Light Source** MBL Medium Base
- Max Watts** 25 75
- Electrical**
 - MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
 - MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



Ordering Guide: Choose from each category, using designated code to specify.

260 STEMT				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Clear tempered glass

Light Source

- MBL13 PAR FL - 13W/30K 1000 Lm PAR30
- MBL13 PAR SP - 13W/30K 1000 Lm PAR30
- MBL13 PAR WFL - 13W/30K 1000 Lm PAR30
- MB25 PAR - 25W MAX. MED base (Par30 lamp by others)
- MB - Maximum 75W Par30 (by others)

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- SSP 120 4KV 120V MOV1 Surge Suppressor