



Cylinder 260 STEMX H: 8.88 W: 4.5 OAL: 24.50

Description

4.5" Square cylinder, suspended by 12" stem with 40° swivel canopy
Designed for use with LED light engines

Specifications

- Housing** Extruded aluminum cylinder with stamped steel canopy*
- Diffuser/Optics** Bare lamp (open aperture)
- Light Source** LED
- Max Watts** 12.99
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only

Ordering Guide: Choose from each category, using designated code to specify.

| | | | | | |
|-----------|----------|--------------|--------|--------|--|
| 260 STEMX | | | | | |
| MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS | |

Diffuser/Optics

Bare-lamp

Light Source

- TL3 HO - 3.04W/40K 982 Lm, 0-10V dimmable
- TL3 - 3.11W/30K 603 Lm, 0-10V dimmable
- TL5 HO - 4.59W/40K 1287 Lm, 120V dimmable
- TL5 - 4.7W/30K 909 Lm, 120V dimmable
- TL6 HO - 6.16W/40K 1588 Lm, 120V dimmable
- TL6 - 6.32W/30K 1208 Lm, 120V dimmable
- TL8 HO - 7.75W/40K 1886 Lm, 120V dimmable
- TL8 - 7.96W/30K 1502 Lm, 120V dimmable
- TL9 HO - 9.36W/40K 2179 Lm, 120V dimmable
- TL10 - 9.62W/30K 1790 Lm, 120V dimmable
- TL11 - 11.3W/30K 2075 Lm, 120V dimmable
- TL13 - 12.99W/30K 2352 Lm, 120V dimmable

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K Non-Stock item - consult factory for availability
- 35K Neutral White
- DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP 10KV 120-277V Supplemental Surge Protection

NOTES:
*Driver is housed in extended aluminum canopy (not shown)