



**Cylinder 260 UDT** H: 12.88 W: 4.50 E: 7 MC: 7

**Description**

4.5" Square Up/Down cylinder wall-mount  
Designed for use with uni-directional LED or reflector type (R/PAR) lamps

**Specifications**

- Housing** Extruded aluminum cylinder with die-cast arm/back
- Diffuser/Optics** Clear tempered glass lens (top & bottom)
- Light Source** MBL Medium Base
- Max Watts** 25 X 2 75 X 2
- Electrical**
  - MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
  - MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



**Ordering Guide:** Choose from each category, using designated code to specify.

260 UDT				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

Clear tempered glass

**Light Source**

- 2MBL13 PAR FL** - 26W/30K 2000 Lm PAR30
- 2MBL13 PAR SP** - 13W/30K 2000 Lm PAR30
- 2MBL13 PAR WFL** - 26W/30K 2000 Lm PAR30
- 2MB25 PAR** - 2x 25W MAX. MED base (lamp by others)
- MB** - Maximum 2x75W Par30 (by others)

**Finish**

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**