



Cylinder 260 UDXT H: 13.5 W: 4.50 E: 9 MC: 7

Description

4.5" Square Downlight cylinder wall-mount
Designed for use with LED light engines

Specifications

- Housing** Extruded aluminum cylinder with die-cast arm/back
- Diffuser/Optics** Clear tempered glass lens (top & bottom)
- Light Source** LED
- Max Watts** 6.32 X 2
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



Ordering Guide: Choose from each category, using designated code to specify.

260 UDXT				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Clear tempered glass

Light Source

- 2TL3 HO - 6.08W/40K 1964 Lm, 0-10V dimmable
- 2TL3 - 3.11W/30K 603 Lm, 0-10V dimmable
- 2TL5 HO - 9.2W/40K 2408 Lm, 120V dimmable
- 2TL5 - 9.4W/30K 1708 Lm, 120V dimmable
- 2TL6 HO - 12.32W/40K 3176 Lm, 120V dimmable
- 2TL6 - 12.64W/30K 2416 Lm, 120V dimmable

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K Non-Stock item - consult factory for availability
- 2DIM010 LED 4-wire 0-10V Dimming - 120-277V
- 35K Neutral White

NOTES: *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)