



Cylinder 260 WMT H: 8.88 W: 4.50 E: 7.8 MC: 2.50

Description

Extruded aluminum cylinder with die-cast arm/back

Specifications

Housing Extruded aluminum cylinder with die-cast arm/back

Diffuser/Optics Clear tempered glass bottom lens

Light Source MBL Medium Base

Max Watts 25 75

Electrical **MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.

Mounting Mounts over 4" recessed outlet box.

Certification Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



Ordering Guide: Choose from each category, using designated code to specify.

260 WMT				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Clear tempered glass

Light Source

- MBL13 PAR FL** - 13W/30K 1000 Lm PAR30
- MBL13 PAR SP** - 13W/30K 1000 Lm PAR30
- MBL13 PAR WFL** - 13W/30K 1000 Lm PAR30
- MB25 PAR** - 25W MAX. MED base (Par30 lamp by others)
- MB** - Maximum 75W Par30 (by others)

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from [Luraline Palette](#)
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

SSP 120 4KV 120V MOV1 Surge Suppressor