



## Cylinder 261 CMXT H: 11.75 W: 6

### Description

6" Square, surface-mounted cylinder  
Designed for use with LED light engines

### Specifications

<b>Housing</b>	Extruded aluminum cylinder with extended canopy (not shown)
<b>Diffuser/Optics</b>	<ul style="list-style-type: none"> <li>• Clear tempered glass bottom lens</li> <li>• Reflector</li> </ul>
<b>Light Source</b>	LED
<b>Max Watts</b>	11.3
<b>Electrical</b>	TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
<b>Mounting</b>	Mounts over 4" recessed outlet box.
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



**Ordering Guide:** Choose from each category, using designated code to specify.

261 CMXT					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

#### Diffuser/Optics

Clear tempered glass  
R - Flood Reflector

#### Light Source

**TL5 HO** - 4.59W/40K 1287 Lm, 120V dimmable  
**TL5** - 4.7W/30K 909 Lm, 120V dimmable  
**TL6 HO** - 6.16W/40K 1588 Lm, 120V dimmable  
**TL8 HO** - 7.75W/40K 1886 Lm, 120V dimmable  
**TL8** - 7.96W/30K 1502 Lm, 120V dimmable  
**TL9 HO** - 9.36W/40K 2179 Lm, 120V dimmable  
**TL10** - 9.62W/30K 1790 Lm, 120V dimmable  
**TL11 HO** - 10.99W/40K 2470 Lm, 120V dimmable  
**TL11** - 11.3W/30K 2075 Lm, 120V dimmable

#### Finish

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

#### Extras (Order Separately)

**27K** Non-Stock item - consult factory for availability  
**35K** Neutral White  
**DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)  
**SSP** 10KV 120-277V Supplemental Surge Protection

NOTES: \*Driver is housed in extended aluminum canopy (not shown)  
 \*Driver is housed in extended aluminum canopy (not shown)  
 \*Driver is housed in extended aluminum canopy (not shown)