



Cylinder 261 CORD H: 9.75 W: 6 OAL: 48.50

Description

6" Square cylinder with reflector, suspended by 36" Black 18-3 cord
 (White cord supplied with white fixtures)
 Designed for use with LED light engines

Specifications

| | | |
|------------------------|---|-------------|
| Housing | Extruded aluminum cylinder with stamped steel canopy | |
| Diffuser/Optics | Bare lamp (open aperture) | |
| Light Source | MBL | Medium Base |
| Max Watts | 25 | 120 |
| Electrical | MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures. | |
| Mounting | Mounts over 4" recessed outlet box. | |
| Certification | Manufactured in accordance with U.L. standard 1598 - For dry locations only | |



Ordering Guide: Choose from each category, using designated code to specify.

| | | | | | |
|----------|----------|--------------|--------|--------|--|
| 261 CORD | | | | | |
| MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS | |

Diffuser/Optics

Bare-lamp

Light Source

MBL15 PAR FL - 15W/30K 1200 Lm PAR38
MBL15 PAR SP - 15W/30K 1200 Lm PAR38
MBL15 PAR WFL - 15W/30K 1200 Lm PAR38
MBL18 PAR FL - 18W/30K 1400 Lm PAR38
MB25 PAR - 25W MAX. MED base (Par38 lamp by others)
MB - Maximum 120W Par38 (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

SSP 120 4KV 120V MOV1 Surge Suppressor