



## Cylinder 261 CORDT H: 10.13 W: 6 OAL: 48.50

### Description

6" Square cylinder with reflector, suspended by 36" Black 18-3 cord  
 (White cord supplied with white fixtures)  
 Designed for use with LED light engines

### Specifications

- Housing** Extruded aluminum cylinder with stamped steel canopy
- Diffuser/Optics** Clear tempered glass bottom lens
- Light Source** MBL Medium Base
- Max Watts** 25 120
- Electrical**
  - MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
  - MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only



### Ordering Guide: Choose from each category, using designated code to specify.

261 CORDT				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

#### Diffuser/Optics

Clear tempered glass

#### Light Source

- MBL15 PAR FL - 15W/30K 1200 Lm PAR38
- MBL15 PAR SP - 15W/30K 1200 Lm PAR38
- MBL15 PAR WFL - 15W/30K 1200 Lm PAR38
- MBL18 PAR FL - 18W/30K 1400 Lm PAR38
- MB25 PAR - 25W MAX. MED base (Par38 lamp by others)
- MB - Maximum 120W Par38 (by others)

#### Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded\***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium\***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- \* Subject to Surcharge

#### Extras (Order Separately)

- SSP 120 4KV 120V MOV1 Surge Suppressor