



Cylinder 261 UDT H: 17.13 W: 6 E: 9.3 MC: 8.56

Description

6" Square Up/Down cylinder wall-mount
Designed for use with uni-directional LED or reflector type (R/PAR) lamps

Specifications

- Housing** Extruded aluminum cylinder with die-cast arm/back
- Diffuser/Optics** Clear tempered glass lens (top & bottom)
- Light Source** MBL Medium Base
- Max Watts** 25 X 2 120 X 2
- Electrical** MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



Ordering Guide: Choose from each category, using designated code to specify.

261 UDT				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Clear tempered glass

Light Source

- 2MBL15 PAR FL - 30W/30K 2400 Lm PAR38
- 2MBL15 PAR SP - 30W/30K 2400 Lm PAR38
- 2MBL15 PAR WFL - 30W/30K 2400 Lm PAR38
- 2MBL18 PAR FL - 36W/30K 2800 Lm PAR38
- 2MB25 PAR - 2x 25W MAX. MED base (lamp by others)
- MB - Maximum 2x120W Par38 (by others)

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)