



Cylinder 261 UDXTR H: 18 W: 6 E: 11.25 MC: 9

Description

6" Square Up/Down cylinder wall-mount w/Reflector
Designed for use with LED light engines or non-reflector type lamps

Specifications

- Housing** Extruded aluminum cylinder with die-cast arm/back
- Diffuser/Optics** Clear tempered glass lens (top & bottom)
- Light Source** LED
- Max Watts** 14.28 X 2
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



Ordering Guide: Choose from each category, using designated code to specify.

261 UDXTR				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Clear tempered glass

Light Source

- 2TL6 HO** - 12.32W/40K 3176 Lm, 120V dimmable
- 2TL6** - 12.64W/30K 2416 Lm, 120V dimmable
- 2TL8 HO** - 15.5W/40K 3772 Lm, 120V dimmable
- 2TL9 HO** - 18.72W/40K 4358 Lm, 120V dimmable
- 2TL10** - 19.24W/30K 3580 Lm, 120V dimmable
- 2TL11 HO** - 21.98W/40K 4970 Lm, 120V dimmable
- 2TL11** - 22.6W/30K 4150 Lm, 120V dimmable
- 2TL13 HO** - 25.32W/40K 5512 Lm, 120V dimmable
- 2TL13** - 25.98W/30K 4704 Lm, 120V dimmable
- 2TL14 HO** - 28.56W/40K 6080 Lm, 120V dimmable

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from [Luraline Palette](#)
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 2DIM010** LED 4-wire 0-10V Dimming - 120-277V
- 35K** Neutral White
- SSP** 10KV 120-277V Supplemental Surge Protection