



## Cylinder 278 STEM H: 7 W: 4.5 OAL: 22.50

### Description

4.5" diameter cylinder, suspended by 12" stem with 40° swivel canopy  
Designed for use with LED light engines

### Specifications

**Housing** Spun aluminum cylinder with stamped steel canopy\*

**Diffuser/Optics** Bare lamp (open aperture)

**Light Source** MBL Medium Base

**Max Watts** 25 75

**Electrical** **MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.  
**MBL** - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.

**Mounting** Mounts over 4" recessed outlet box.

**Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



**Ordering Guide:** Choose from each category, using designated code to specify.

|          |          |              |        |        |
|----------|----------|--------------|--------|--------|
| 278 STEM |          |              |        |        |
| MODEL    | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |

#### Diffuser/Optics

- Bare-lamp (open aperture)

#### Light Source

**MBL13 PAR FL** - 13W/30K 1000 Lm PAR30  
**MBL13 PAR SP** - 13W/30K 1000 Lm PAR30  
**MBL13 PAR WFL** - 13W/30K 1000 Lm PAR30  
**MB25 PAR** - 25W MAX. MED base (Par30 lamp by others)  
**MB** - Maximum 75W Par30 (by others)

#### Finish

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
\* Subject to Surcharge

#### Extras (Order Separately)

**SSP 120** 4KV 120V MOV1 Surge Suppressor

#### NOTES:

- \*Driver is housed in extended aluminum canopy (not shown)
- \*Driver is housed in extended aluminum canopy (not shown)
- \*Driver is housed in extended aluminum canopy (not shown)
- \*Driver is housed in extended aluminum canopy (not shown)