



Cylinder 278 STEMT H: 7 W: 4.5 OAL: 22.50

Description

4.5" diameter cylinder, suspended by 12" stem with 40° swivel canopy
Designed for use with LED light engines

Specifications

Housing	Spun aluminum cylinder with stamped steel canopy*		
Diffuser/Optics	Clear tempered glass bottom lens		
Light Source	MBL	Medium Base	
Max Watts	25	75	
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.		
Mounting	Mounts over 4" recessed outlet box.		
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations		

Ordering Guide: Choose from each category, using designated code to specify.

278 STEMT

MODEL DIFFUSER LIGHT SOURCE FINISH EXTRAS

Diffuser/Optics
Clear tempered glass

Light Source
MBL13 PAR FL - 13W/30K 1000 Lm PAR30
MBL13 PAR SP - 13W/30K 1000 Lm PAR30
MBL13 PAR WFL - 13W/30K 1000 Lm PAR30
MB25 PAR - 25W MAX. MED base (Par38 lamp by others)
MB - Maximum 75W Par30 (by others)

Finish
Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)
SSP 120 4KV 120V MOV1 Surge Suppressor