



Cylinder 278 UD H: 12.88 W: 4.50 E: 7.50 MC: 6.44

Description

4.5" Diameter Up/Down cylinder wall-mount
Designed for use with uni-directional LED or reflector type (R/PAR) lamps

Specifications

Housing	Extruded aluminum cylinder with die-cast arm/back	
Diffuser/Optics	Bare lamp (open aperture)	
Light Source	MBL	Medium Base
Max Watts	25 X 2	75 X 2
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.	
Mounting	Mounts over 4" recessed outlet box.	
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only	



Ordering Guide: Choose from each category, using designated code to specify.

278 UD				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- Bare-lamp (open aperture)

Light Source

2MBL13 PAR FL - 26W/30K 2000 Lm PAR30
2MBL13 PAR SP - 13W/30K 2000 Lm PAR30
2MBL13 PAR WFL - 26W/30K 2000 Lm PAR30
2MB25 PAR - 2x 25W MAX. MED base (lamp by others)
MB - Maximum 2x75W Par30 (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)