



**Cylinder 278 UDX** H: 12.88 W: 4.50 E: 9.56 MC: 6.44

### Description

4.5" Diameter Up/Down cylinder wall-mount  
Designed for use with LED light engines

### Specifications

- Housing** Extruded aluminum cylinder with die-cast arm/back
- Diffuser/Optics**
  - Bare lamp (open aperture)
  - Reflector
- Light Source** LED
- Max Watts** 6.32 X 2
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only



**Ordering Guide:** Choose from each category, using designated code to specify.

278 UDX				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

#### Diffuser/Optics

- Bare-lamp (open aperture)
- R** - Flood Reflector

#### Light Source

- 2TL3 HO** - 6.08W/40K 1964 Lm, 0-10V dimmable
- 2TL3** - 3.11W/30K 603 Lm, 0-10V dimmable
- 2TL5 HO** - 9.2W/40K 2408 Lm, 120V dimmable
- 2TL5** - 9.4W/30K 1708 Lm, 120V dimmable
- 2TL6 HO** - 12.32W/40K 3176 Lm, 120V dimmable
- 2TL6** - 12.64W/30K 2416 Lm, 120V dimmable

#### Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

#### Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection