



**Cylinder 278 WM** H: 7 W: 4.50 E: 7 MC: 2.50

**Description**

4.5" Diameter Downlight cylinder wall-mount  
Designed for use with uni-directional LED or reflector type (R/PAR) lamps

**Specifications**

- Housing** Spun aluminum cylinder with die-cast arm/back
- Diffuser/Optics** Bare lamp (open aperture)
- Light Source** MBL Medium Base
- Max Watts** 25 75
- Electrical** MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.  
MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only



**Ordering Guide:** Choose from each category, using designated code to specify.

278 WM				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

- Bare-lamp (open aperture)

**Light Source**

- MBL13 PAR FL** - 13W/30K 1000 Lm PAR30
- MBL13 PAR SP** - 13W/30K 1000 Lm PAR30
- MBL13 PAR WFL** - 13W/30K 1000 Lm PAR30
- MB25 PAR** - 25W MAX. MED base (Par30 lamp by others)
- MB** - Maximum 75W Par30 (by others)

**Finish**

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**