



Cylinder 279 STEM H: 9 W: 6 OAL: 22.75

Description

6" diameter cylinder, suspended by 12" stem with 40° swivel canopy
 Designed for use with uni-directional LED or reflector type (R/PAR) lamps

Specifications

- Housing** Spun aluminum cylinder with stamped steel canopy
- Diffuser/Optics** Bare lamp (open aperture)
- Light Source** MBL Medium Base
- Max Watts** 25 120
- Electrical**
 - MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
 - MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



Ordering Guide: Choose from each category, using designated code to specify.

279 STEM				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- Bare-lamp (open aperture)

Light Source

- MBL15 PAR FL - 15W/30K 1200 Lm PAR38
- MBL15 PAR SP - 15W/30K 1200 Lm PAR38
- MBL15 PAR WFL - 15W/30K 1200 Lm PAR38
- MBL18 PAR FL - 18W/30K 1400 Lm PAR38
- MB25 PAR - 25W MAX. MED base (Par38 lamp by others)
- MB - Maximum 120W Par38 (by others)

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- B79 Black milli-groove baffle (Not Available with Tempered glass lens)
- SSP 120 4KV 120V MOV1 Surge Suppressor