



Cylinder 279 UDT H: 17.12 W: 6 E: 8.50 MC: 8.56

Description

6" Diameter Up/Down cylinder wall-mount
Designed for use with uni-directional LED or reflector type (R/PAR) lamps

Specifications

- Housing** Extruded aluminum cylinder with die-cast arm/back
- Diffuser/Optics** Clear tempered glass lens (top & bottom)
- Light Source** MBL Medium Base
- Max Watts** 25 X 2 120 X 2
- Electrical** MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



Ordering Guide: Choose from each category, using designated code to specify.

279 UDT				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- Clear Tempered Glass

Light Source

2MBL15 PAR FL - 30W/30K 2400 Lm PAR38
2MBL15 PAR SP - 30W/30K 2400 Lm PAR38
2MBL15 PAR WFL - 30W/30K 2400 Lm PAR38
2MBL18 PAR FL - 36W/30K 2800 Lm PAR38
2MB25 PAR - 2x 25W MAX. MED base (lamp by others)
MB - Maximum 2x120W Par38 (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)