



Cylinder 279 WMT H: 9 W: 6 E: 8.50 MC: 4

Description

6" Diameter Downlight cylinder wall-mount
 Designed for use with uni-directional LED or reflector type (R/PAR) lamps

Specifications

Housing	Spun aluminum cylinder with die-cast arm/back		
Diffuser/Optics	Clear tempered glass bottom lens		
Light Source	MBL	Medium Base	
Max Watts	25	120	
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.		
Mounting	Mounts over 4" recessed outlet box.		
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations		

Ordering Guide: Choose from each category, using designated code to specify.

279 WMT

MODEL DIFFUSER LIGHT SOURCE FINISH EXTRAS

Diffuser/Optics

Clear tempered glass

Light Source

- MBL15 PAR SP** - 15W/30K 1200 Lm PAR38
- MBL15 PAR WFL** - 15W/30K 1200 Lm PAR38
- MBL15 PAR FL** - 15W/30K 1200 Lm PAR38
- MBL18 PAR FL** - 18W/30K 1400 Lm PAR38
- MB25 PAR** - 25W MAX. MED base (Par38 lamp by others)
- MB** - Maximum 120W Par38 (by others)

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

B79 Black milli-groove baffle
 (Not Available with Tempered glass lens)