



**Cylinder 288 CMX** H: 12.88 W: 8

**Description**

8" Square, surface-mounted cylinder  
Designed for use with LED light engines

**Specifications**

- Housing** Extruded aluminum cylinder with extended canopy\*
- Diffuser/Optics** • Bare lamp (open aperture) - For LENSED aperture, see Model No. 288 WMXT  
• Reflector
- Electrical** TL/HO- L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only

**Ordering Guide:** Choose from each category, using designated code to specify.



**Diffuser/Optics**

- Bare-lamp (open aperture)
- R** - Flood Reflector

**Light Source**

**Finish**

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection

NOTES:  
\*Driver is housed in extended aluminum canopy (not shown)