



Cylinder 288 UDXT H: 19 W: 8 E: 14.25 MC: 9.7

Description

8" Square Up/Down cylinder wall-mount

Specifications

- Housing** Fabricated aluminum cylinder with die-cast arm/back
- Diffuser/Optics** Clear tempered glass lens (top & bottom)
- Light Source** LED
- Max Watts** 26.16 X 2
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



Ordering Guide: Choose from each category, using designated code to specify.

288 UDXT					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

Clear tempered glass

Light Source

- 2TL14 HO** - 28.56W/40K 6080 Lm, 120V dimmable
- 2TL15** - 29.78W/30K 5252 Lm, 120V dimmable
- 2TL16.0 HO** - 31.88W/40K 6640 Lm, 120V dimmable
- 2TL16** - 32.82W/30K 5790 Lm, 120V dimmable
- 2TL19 HO** - 39.76W/40K 7742 Lm, 0-10V dimmable
- 2TL20** - 39.76W/30K 6842 Lm, 0-10V dimmable
- 2TL23 HO** - 45.42W/40K 8820 Lm, 0-10V dimmable
- 2TL26 HO** - 52.32W/40K 9876 Lm, 0-10V dimmable

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 2DIM010** LED 4-wire 0-10V Dimming - 120-277V
- 35K** Neutral White
- SSP** 10KV 120-277V Supplemental Surge Protection

NOTES: *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)