



Cylinder 290 CMXT H: 13.19 W: 8

Description

8" Diameter, surface-mounted cylinder
Designed for use with LED light engines

Specifications

- Housing** Aluminum cylinder with extended canopy.
- Diffuser/Optics**
 - Reflector
 - Tempered Glass
- Light Source** LED
- Max Watts** 34.95
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



Ordering Guide: Choose from each category, using designated code to specify.

290 CMXT					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

- Clear Tempered Glass
- R - Flood Reflector

Light Source

- TL13 HO - 12.62W/40K 2756 Lm, 120V dimmable
- TL13 - 12.99W/30K 2352 Lm, 120V dimmable
- TL14 HO - 14.28W/40K 3040 Lm, 120V dimmable
- TL15 - 14.69W/30K 2626 Lm, 120V dimmable
- TL16 HO - 15.94W/40K 3320 Lm, 120V dimmable
- TL16 - 16.41W/30K 2895 Lm, 120V dimmable
- TL19 HO - 19.3W/40K 3871 Lm, 120V dimmable
- TL20 - 19.9W/30K 3421 Lm, 0-10V dimmable
- TL23 HO - 22.71W/40K 4410 Lm, 0-10V dimmable
- TL26 HO - 26.16W/40K 4938 Lm, 0-10V dimmable
- TL27 - 26.98W/30K 4428 Lm, 0-10V dimmable
- TL31 - 30.6W/30K 4913 Lm, 0-10V dimmable
- TL35 HO - 34.95W/40K 6213 Lm, 0-10V dimmable

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K Non-Stock item - consult factory for availability
- 35K Neutral White
- B90 Black milli-groove baffle (Not Available with Tempered glass lens)
- DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP 10KV 120-277V Supplemental Surge Protection

NOTES: *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)