



**Cylinder 290 CORDT** H: 13.25 W: 8 OAL: 51

**Description**

8" diameter cylinder, suspended by 36" Black 18-3 cord  
 (White cord supplied with white fixtures)  
 Designed for use with uni-directional LED or reflector type (R/PAR) lamps

**Specifications**

- Housing** Spun aluminum cylinder with stamped steel canopy
- Diffuser/Optics** Clear tempered glass bottom lens
- Light Source** MBL Medium Base
- Max Watts** 25 120
- Electrical**
  - MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
  - MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only



**Ordering Guide:** Choose from each category, using designated code to specify.

290 CORDT				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

Clear tempered glass

**Light Source**

- MBL15 PAR FL** - 15W/30K 1200 Lm PAR38
- MBL15 PAR SP** - 15W/30K 1200 Lm PAR38
- MBL15 PAR WFL** - 15W/30K 1200 Lm PAR38
- MBL18 PAR FL** - 18W/30K 1400 Lm PAR38
- MB25 PAR** - 25W MAX. MED base (Par38 lamp by others)
- MB** - Maximum 120W Par38 (by others)

**Finish**

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**

- B90** Black milli-groove baffle (Not Available with Tempered glass lens)
- SSP 120** 4KV 120V MOV1 Surge Suppressor