



**Cylinder 290 CORDX** H: 12.88 W: 8 OAL: 52.5

### Description

8" diameter cylinder, suspended by 36" Black 18-3 cord  
 (White cord supplied with white fixtures)  
 Designed for use with uni-directional LED or reflector type (R/PAR) lamps

### Specifications

<b>Housing</b>	Spun aluminum cylinder with stamped steel canopy*
<b>Diffuser/Optics</b>	• Bare lamp (open aperture) • Reflector
<b>Light Source</b>	LED
<b>Max Watts</b>	36.12
<b>Electrical</b>	TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
<b>Mounting</b>	Mounts over 4" recessed outlet box.
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - For dry locations only

**Ordering Guide:** Choose from each category, using designated code to specify.

290 CORDX				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

#### Diffuser/Optics

- Bare-lamp (open aperture)
- R** - Flood Reflector

#### Light Source

- TL11 HO** - 10.99W/40K 2470 Lm, 120V dimmable
- TL13 HO** - 12.62W/40K 2756 Lm, 120V dimmable
- TL14 HO** - 14.28W/40K 3040 Lm, 120V dimmable
- TL16 HO** - 15.94W/40K 3320 Lm, 120V dimmable
- TL16** - 16.41W/30K 2895 Lm, 120V dimmable
- TL19 HO** - 19.3W/40K 3871 Lm, 120V dimmable
- TL23 HO** - 22.71W/40K 4410 Lm, 0-10V dimmable
- TL31** - 30.6W/30K 4913 Lm, 0-10V dimmable
- TL36** - 36.12W/30K 5620 Lm, 0-10V dimmable

#### Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - [Specify Color #](#)
- UPG** - [Select Color from Luraline Palette](#)
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

#### Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection

NOTES:  
 \*Driver is housed in extended aluminum canopy (not shown)