



Cylinder 290 CORDXT H: 13.25 W: 8 OAL: 52.75

Description

8" diameter cylinder, suspended by 36" Black 18-3 cord
 (White cord supplied with white fixtures)
 Designed for use with uni-directional LED or reflector type (R/PAR) lamps

Specifications

| | |
|------------------------|---|
| Housing | Spun aluminum cylinder with stamped steel canopy* |
| Diffuser/Optics | • Clear tempered glass bottom lens • Reflector |
| Light Source | LED |
| Max Watts | 22.71 |
| Electrical | TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent). |
| Mounting | Mounts over 4" recessed outlet box. |
| Certification | Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations |

Ordering Guide: Choose from each category, using designated code to specify.

| | | | | |
|------------|----------|--------------|--------|--------|
| 290 CORDXT | | | | |
| MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |

Diffuser/Optics

Clear tempered glass
R - Flood Reflector

Light Source

TL11 HO - 10.99W/40K 2470 Lm, 120V dimmable
TL13 HO - 12.62W/40K 2756 Lm, 120V dimmable
TL14 HO - 14.28W/40K 3040 Lm, 120V dimmable
TL16 HO - 15.94W/40K 3320 Lm, 120V dimmable
TL16 - 16.41W/30K 2895 Lm, 120V dimmable
TL19 HO - 19.3W/40K 3871 Lm, 120V dimmable
TL23 HO - 22.71W/40K 4410 Lm, 0-10V dimmable

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - [Specify Color #](#)
UPG - Select Color from [Luraline Palette](#)
Premium*
CCM - Custom Color
CIC - [Inner Color](#)
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

27K Non-Stock item - consult factory for availability
35K Neutral White
B90 Black milli-groove baffle (Not Available with Tempered glass lens)
DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
SSP 10KV 120-277V Supplemental Surge Protection

NOTES:
 *Driver is housed in extended aluminum canopy (not shown)